

CSC900StairClimber-BuiltforPerformance, Engineered for Endurance

The Spirit Fitness CSC900 StairClimber delivers a high-intensity, results-driven cardio experience built for both commercial durability and user comfort. Its industrial-grade chain and poly-v belt drive system powers oversized steps through a precision-controlled Electro-Magnetic Induction Brake—ensuring smooth, consistent performance through years of heavy use.

With a massive step profile—among the largest in its class—and boasting a 8"H (20 cm) step height, the CSC900 offers unmatched stability and versatility, accommodating advanced movement patterns like side crossovers while reducing risk of misstep. The eight-step rotation provides a continuous climbing motion, reaching speeds of 150+ steps per minute, across 20 resistance levels and 12 pre-set programs to challenge every fitness level.

Ergonomically positioned multi-grip handlebars integrate contact heart rate sensors, resistance toggles, and start/stop/pause buttons—keeping performance at your fingertips. A minimum ceiling height of 10' (3 m) is required for safe use.

The CSC900 is the ultimate stair climbing solution for commercial fitness environments that demand lasting performance and dynamic training variety.

CSC900 STAIRCLIMBER

- Durable steel frame with 8 ABS steps
- Large step surface area, 21.5"W x 11"D x 8" H (55W x 28D x 20H cm)
- 20 levels of resistance with step rate of 25 to 160 steps per minute
- 12 pre-loaded programs
- Contact heart rate grips, resistance controls, and start/stop/pause button on handlebars
- Reading/accessory rack





CSC900 STAIRCLIMBER

EQUIPMENT SPECIFICATIONS

Console Multi-window white LED display with built in fan, integrated tablet

rack, and space for accessories

Programs Warm up, WFI and CPAT training, fitness test, fat burn, rolling hills, challenge, interval, target (3 options), user program

Heart Rate Hand pulse sensors

Resistance 20 levels

Step Dimensions 21.5"D x 11"W x 8"H (9" initial step-up height) / 55D x 28W x 20H cm (23 cm initial step-up height)

Power AC adapter; 100-240V **Step Rate** 25 to 160 steps per minute

Remote Buttons Resistance up/down, start/stop/pause

Minimum Ceiling 10 ft (3 M)

Frame Commercial-grade steel with plastic shrouds and maintenance access panels

Dimensions 64" L x 38" W x 83" H, 506 lb (163 L x 97 W x 211 H cm, 230 kg)

Packaging 64" L x 56" W x 44" H, 704 lb (163 L x 142 W x 112 H cm, 320 kg)

Max User Weight 400 lb (182 kg)

WARRANTY INFORMATION

Commercial (All Facilities) - Frame: 10 Years, Brake: 5 Years, Parts/Labour: 3 Years, Wear Items: 6 Months